

FORK OIL FL VERY LIGHT 2.5W

**High Performance Hydraulic Fluid for any telescopic fork
100% Synthetic
Very Light**

TYPE OF USE

Fluides hydraulique pour applications racing.

Spécialement formulé pour les fourches KAYABA, SHOWA, OHLINS, WP et tout autre type de fourches télescopique inversées ou conventionnelles.

PERFORMANCES

Reduced internal friction, specially fork tubes and seals thanks to the exclusive anti-friction additive designed and developed by MOTUL.

Outstanding suspension performance as soon as riding and maintained performance in time.

High performance anti-foam avoiding air transfer to the air chamber to maintain suspension performance.

Anti-wear and extreme pressure properties. Anti-corrosion. Seals protection.

RECOMMENDATIONS

Les huiles de fourches MOTUL Fork Oil Factory Line peuvent être mélangées pour obtenir l'amortissement optimum souhaité.

Utiliser la quantité exacte préconisée par le constructeur.

PROPERTIES

Grade de viscosité		2.5W
Densité à 20°C	ASTM D1298	0.834
Viscosité à 40°C (104°F)	ASTM D445	15.0 mm ² /s
Viscosité à 100°C (212°F)	ASTM D445	3.5 mm ² /s
Indice de viscosité	ASTM D2270	112.0

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development. br>

Product specifications are definitive from the order which is subject to our general conditions of sale and warranty. Made in FRANCE

MOTUL - 119 Bd Félix Faure - 93303 - Aubervilliers Cedex - BP 94 - FRANCE - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 -



FORK OIL FL VERY LIGHT 2.5W

High Performance Hydraulic Fluid for any telescopic fork
100% Synthetic
Very Light

Point d'écoulement	ASTM D97	-39.0 °C / -38.0 °F
Point éclair	ASTM D92	205.0 °C / 401.0 °F